



LT240

LT240

Floor Plate Two Post Lift



Scan for more information

The LT240 is a floor plate two post lift equipped with an electric hydraulic power system. Its steel structural columns are formed by thickened steel plate stamping and bending, and the exterior is treated with full powder coating, ensuring durability and longevity.



4.0T Lifting Capacity



Pre-set Hydraulic Overload Protection



Full Mechanical Safety Device



Features

1. Lifting capacity of up to 4.0T, catering to common passenger car maintenance scenarios.
2. Adjustable tray with a minimum height of 100mm, suitable for sports car lifting;
3. 120% dynamic and 150% static load testing compliant with CE standards;
4. Pre-set rated hydraulic pressure with overload protection when lifting vehicles;
5. Column width of 2780mm, suitable for wide vehicles like SUVs and commercial vans;
6. Full-travel mechanical safety locks for easy and secure operation;
7. Professional cloth protective design, rubber door guard pads, foot protection bars, explosion-proof flow control valves;
8. All movable points use automatic lubrication oil-free bearings to ensure long-lasting durability.

Parameters

Power Supply	220V/380V	Lifting Time	≤ 50S
Max Lifting Weight	4.0T	Drive Mode	hydraulic drive
Max Lifting Height	1930mm	Machine Power	2.2kw
Min Lifting Height	100mm	Hydraulic Oil	8Lwear-resistant hydraulic oil, provided by users
Total Height	2824mm	Hydraulic Power Unit	2.7ml/r
Distance between Columns	2780mm	Work Environment	Temperature: 5~40°C Humidity: 30~95%