



LT445

LT445

Four Post Lift



Scan for more information

LT445 is a fully automatic control insurance wheel alignment four post lift, equipped with an electronically controlled pneumatic insurance device. This enhances the overall high-level experience and convenience of use. It comes with insurance detection equipment, ensuring safety and reliability. The composite reinforced bridge plate design adds robust support.



4.5T Lifting Capacity



Pneumatic Unlocking with Detection Ensures That the Bridge Plate is Level



Equipped With Secondary Lifting Mobile Trolley



Features

1. The oil cylinder parts are processed by high-speed fully automatic CNC lathes. It ensures excellent concentricity and smoothness, and the cylinder barrel is rolled and mirrored.
2. Electro-hydraulic system, wire rope transmission, enlarged oil cylinder for smooth lifting and lowering.
3. Shot blasting surface treatment, high-temperature spray treatment, and durability guaranteed.
4. Four-sided wire rope balance, very suitable for four-wheel alignment.
5. Fully automatic control of pneumatic unlocking belt detection.

Parameters

Power Supply	220V/380V	Inner Distance of Runway	910~1010mm
Main Unit Rated Lifting Weight	4500kg	Net Weight	1245kg
Trolley Rated Lifting Weight	2000kg	Power	2.2kw
Initial Height	210mm	Drive Mode	Electro-hydraulic
Main Lift Lifting Height	1700mm	Hydraulic Oil	10L 46# Antl-wear hydraulic oll (self-purchase)
Jacking Beam Rise	480mm	Air Pressure	6~8bar
Platform Length	4510mm	Working Temperature	5~40°C
Distance Between Columns	2830mm		